Application No.: Not Yet Assigned Docket No.: 30051/39759

Amendments to the CLAIMS

Please delete the centered heading Patent Claims.

Before claim 1, please insert the following heading at the left-hand margin: I Claim:

Please amend the claims as follows:

- 1. (Currently amended): A coffee machine (1) for preparing at least a first coffee beverage at a first brewing pressure and at least a second coffee beverage at a second brewing pressure, the second brewing pressure being higher than the first brewing pressure, comprising a brewing means (5) which is connected via an outlet line (9) to a tap opening (1), and a throttle means (12,112) which is provided in the outlet line (9) and which is adjustable between a first and a second flow cross-section, the first flow cross-section being greater than the second flow cross-section, characterized in that and the throttle means (12, 112) is adjustable by the action of the brewing pressure.
- 2. (Currently amended): The coffee machine according to claim 1, characterized in that wherein the throttle means (12, 112) is adjustable by the higher brewing pressure.
- 3. (Currently amended): The coffee machine according to claim 1 or 2, characterized in that wherein the throttle means (12, 112) comprises a piston (16, 116) with a piston surface (17) which can be actuated by the brewing pressure for moving the piston (16, 116) in one direction, and a motion means (19) for moving the piston (16, 116) in the opposite direction.
- 4. (Currently amended): The coffee machine according to claim 3, characterized in that wherein the motion means includes a spring (19) having a force greater than the lower brewing pressure exerted on the throttle means (12, 112), but smaller than the higher brewing pressure.
- 5. (Currently amended): The coffee machine according to claim 3 or 4; eharacterized in that whrein the piston (16, 116) has a sealing surface (22, 122) closing the larger flow cross-section.

Application No.: Not Yet Assigned Docket No.: 30051/39759

6. (Currently amended): The coffee machine according to any one of claims 3 to 5, characterized in that claim 3, and a passage (24, 124) defining the smaller passage cross-section is assigned to the piston (16, 116).

- 7. (Currently amended): The coffee machine according to any one of claims 1 to 6, characterized in that claim 1, wherein the smaller flow cross-section is defined by a permanently open passage (24, 124) and the larger flow cross-section by the passage (24, 124) and a closable flow path (21) surrounding the passage (24, 124).
- 8. (Currently amended): The coffee machine according to any one of claims 1 to 7, eharacterized in that claim 1, wherein the throttle means (12, 112) includes a housing (13) having an inlet (14) and an outlet (15) in which a piston is movable with a piston surface (17) facing the inlet (14) and with a sealing surface (22, 122) which faces the outlet (15) and is engageable with a sealing seat (23 123) defining the larger flow cross-section, a flow path (21) being provided between the inlet (14) and the sealing seat (23, 123) between the outer surface of the piston (16, 116) and the inner surface of the housing (13).
- 9. (Currently amended): The coffee machine according to any one of claims 6 to 8, eharacterized in that claim 6, wherein the passage (24) is a through-hole extending through the piston (16).
- 10. (Currently amended): The coffee machine according to any one of claims 6 to 8, characterized in that claim 6, wherein the passage (124) is formed by at least one passage opening between a sealing surface (122) provided on the piston (116) and an associated sealing seat (123).